



**ARTEL**

**NIEUW IN HET  
ASSORTIMENT**



**Pelletkachel  
Cayenne**



CAYENNE		14		14 DUCTED		16		16 DUCTED	
	Eenheid	Max	Min	Max	Min	Max	Min	Max	Min
 <b>POWER</b> Vermogen	kW	13.2	3.8	13.2	3.8	16.3	3.8	16.3	3.8
 <b>Rendement</b>	%	98	93.5	98	93.5	98	93.5	98	93.5
 <b>Rookgas Temp.</b>	°C	135	80	135	80	135	80	135	80
 <b>Afvoer Diam</b>	mm	Ø 80		Ø 80		Ø 80		Ø 80	
 <b>Inlaat Diam.</b>	mm	Ø 50		Ø 50		Ø 50		Ø 50	
 <b>Pellettank Inh.</b>	kg	23		23		23		23	
 <b>Pellet diameter</b>	mm	Ø 6		Ø 6		Ø 6		Ø 6	
 <b>Verbruik / uur</b>	kg/h	1,3	0,3	1,65	0,5	2	0,5	2,4	0,5
 <b>Branduren/tank</b>	h	29	8	29	8	29	7	29	7
 <b>Oppervlakte</b>	m <sup>2</sup>	* 100		* 100		150		150	
 <b>Kg Gewicht</b>	kg	105		110		105		110	
 <b>DUCTED</b>	Aantal	0		2		0		2	
<b>Afmeting</b>	<b>HxBxD</b>	1015x495x58 0		970x475x500		1060x475x500		1060x475x500	
<b>Keramische gloeikaars</b>	<b>Ja/Nee</b>	Nee		Nee		Nee		Nee	

\*1 Verwarmbaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning met standaard kamerhoogte van ± 260 cm.