


















ARTEL

**NIEUW IN HET
ASSORTIMENT**



**Moederhaard
Redonda**



	Redonda	16 kW		20 kW		24 kW	
	Eenheid	Max	Min	Max	Min	Max	Min
 POWER Vermogen	kW	17.1	5.1	19.0	5.26	23.12	5.26
 POWER Verm. water	kW	16.1	4.9	18.4	4.2	21.96	5.08
 Rendement	%	95.9	94.5	96.7	95.7	96.7	94.9
 Rookgas Temp.	°C	130	63	135	63	140	63
 Min. afv. druk	Pa	12	12	12	12	12	12
 Afvoer Diam.	mm	Ø 80		Ø 80		Ø 80	
 Inlaat Diam.	mm	Ø 50		Ø 50		Ø 50	
 CV aansluiting	Inch	3/4		3/4		3/4	
 Ketel Liter inh.	l	25		25		25	
 Pellettank Inh.	kg	33		38		38	
 Pellet diameter	mm	Ø 6		Ø 6		Ø 6	
 Verbruik / uur	kg/h	3.5	1.04	4.0	1.1	4.9	1.11
 Branduren/tank	h	31	9.5	34	9.5	34	7.5
 Oppervlakte	m ³	* 300		* 400		* 500	
 Gewicht	kg	160		230		230	
Afmeting	HxBxD	1190x610x 770		1280x650x 760		1280x650x 760	

* Verwarmbaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning.